

# VITODENS 300

# VIESSMANN

P <sub>min.</sub> (80/60 °C)	6,0 kW	P <sub>max.</sub> (80/60 °C)	23,7 kW
P <sub>min.</sub> (50/30 °C)	6,6 kW	P <sub>max.</sub> (50/30 °C)	26,0 kW
Q <sub>min.</sub> (H <sub>i</sub> )	6,3 kW	Q <sub>max.</sub> (H <sub>i</sub> )	24,7 kW

B23, B33, C13X, C33X, C43X, C53X, C63X, C83X

	Kategorie	Gasart	P <sub>n</sub>
DE	II <sub>2</sub> ELL3P	G 20 / G 25 / G 31	20 / 50 mbar
AT, HR, RU, SI, SK, TR	II <sub>2</sub> H3P	G 20 / G 31	20 / 50 mbar
BE	I <sub>2</sub> E(S)B - I <sub>3</sub> P	G 20 / G 25 / G 31	20 / 25 / 37 mbar
CH, CZ, ES, GB, IT	II <sub>2</sub> H3P	G 20 / G 31	20 / 37 mbar
DK	II <sub>2</sub> H3P	G 20 / G 31	20 / 30 mbar
FR	II <sub>2</sub> E(R)B3P	G 20 / G 25 / G 31	20 / 25 / 37 mbar
HU	II <sub>2</sub> HS3P	G 20 / G 25.1 / G 31	20 / 25 / 50 mbar
PL	II <sub>2</sub> HLL3P	GZ 50 / GZ 41,5 / G 31	20 / 50 mbar

P<sub>MS</sub>

3 bar

P<sub>MW</sub>

10 bar

D

11,2 l/m<sup>3</sup>n

NO<sub>x</sub>-Klasse

5

AT: ÖVGW-Reg.-Nr.

G 2.628

230 V~ / 50 Hz / IPX4D / max. 165 W